

Rec'd PATENTS 27 DEC 2004

519254

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
15 April 2004 (15.04.2004)

PCT

(10) International Publication Number  
WO 2004/031585 A1

(51) International Patent Classification<sup>7</sup>: F04C 18/18

Kozo [JP/JP]; c/o Ebara Densan Ltd., 11-1, Haneda Asahi-cho, Ohta-ku, Tokyo 144-8575 (JP).

(21) International Application Number:  
PCT/JP2003/012652

(74) Agents: WATANABE, Isamu et al.; GOWA Nishi-Shinjuku 4F, 5-8, Nishi-Shinjuku 7-chome, Shinjuku-ku, Tokyo 160-0023 (JP).

(22) International Filing Date: 2 October 2003 (02.10.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
2002-292889 4 October 2002 (04.10.2002) JP

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(71) Applicants (*for all designated States except US*): EBARA DENSAN LTD. [JP/JP]; 11-1, Haneda Asahi-cho, Ohta-ku, Tokyo 144-8575 (JP). EBARA CORPORATION [JP/JP]; 11-1, Haneda Asahi-cho, Ohta-ku, Tokyo 144-8510 (JP).

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(72) Inventors; and


(75) Inventors/Applicants (*for US only*): MIYASHITA, Nobuhito [JP/JP]; c/o Ebara Densan Ltd., 11-1, Haneda Asahi-cho, Ohta-ku, Tokyo 144-8575 (JP). MATAKE,

Published:

— with international search report

[Continued on next page]

(54) Title: SCREW PUMP AND METHOD OF OPERATING THE SAME



(57) Abstract: A screw pump includes a pair of screw rotors (2a, 2b) having teeth which are held in mesh with each other for drawing and discharging a fluid by rotating the screw rotors (2a, 2b) synchronously in opposite directions. The teeth of the screw rotors (2a, 2b) have the same shape as each other and are coiled helically in opposite directions. The teeth of the screw rotors (2a, 2b) have an axial tooth profile which allows a pair of facing teeth surfaces T of the screw rotors (2a, 2b) to be brought into contact with each other only at a pitch line P when the pair of facing teeth surfaces T are brought into contact with each other.

WO 2004/031585 A1